

## **COSMOPLAST 763**

### **Tool cleaner**

#### APPLICATION

**COSMOPLAST 763** is mainly used to clean from the tools and application devices remainders of not hardened up 1- and 2-component PUR- and 2-component epoxy reaction adhesives. – For professional use by instructed personnel only.

**COSMOPLAST 763** also dissolves partly or fully hardened up adhesives.

**COSMOPLAST 763** is very economical in use, because of its intensive cleaning effect and because of its high boiling point.

#### TECHNICAL DATA

BASIS	mixture based on derivatives of carboxylic acid VOC free acc. to the Switzerland VOC Directives		
DENSITY	according to EN 542 at +20°C	approx.	1,10 g/cm <sup>3</sup>
FLASH POINT			+103°C
IGNITION TEMPERATURE			+370°C
MINIMUM TEMPERATURE FOR APPLICATION		from	+5 °C

#### WORKING INSTRUCTIONS

1- and 2-component PUR adhesives and 2-component epoxy reaction adhesives are cleaned with **COSMOPLAST 763** from the tools or adhesive substrates, when they are fresh or only partly hardened up, by means of a brush.

Because of the slow evaporation of **COSMOPLAST 763**, it is recommended to clean afterwards the material surface with **COSMOFEN 60**.

\* Tools, which have been moistened with 1-component PUR adhesives, can be stored until the following day in a cleaning bath with **COSMOPLAST 1620**, in order to delay a further reaction of the adhesive system.

\* **COSMOPLAST 763** should not be used for the preliminary cleaning of substrate adhesive surfaces!

\* Because of the strong cleaning effect of **COSMOPLAST 763**, it should be checked before the application, whether the concerned lacquer, plastic material, sealing, rubber roll, etc. are therefore resistant enough!

#### STORAGE

Store **COSMOPLAST 763** in tightly closed original casks, in a dry place, at a temperature between +15°C and +25°C, without direct solar irradiation.

Can be stored in unopened original casks for approx. 24 months.

**COSMOPLAST 763**  
**Tool cleaner**

page 2

CASK SIZE10l metal canister  
200l metal bung hole drum**Accessory:**

As accessory, we deliver our non-staining **cellulose cleaning clothes** on a perforated big roll with **practical paper dispenser**.

CLASSIFICATION

**Information can be taken from the safety data sheet.**

*Our instructions for use, processing directives, product- or performance indications, as well as other technical statements are only general guidelines; they only describe the nature of our products (determined value at the production time) and their performance, but they give no guarantee in accordance with paragraph 443 of the BGB (Civil Code). Due to the variety of application purposes for each product, and due to a lot of different particular conditions (e. g. processing parameters, material properties, etc.), the user has to carry out his own individual qualifying tests. Our consultation in application technique, verbal and in writing, as well as with tests, is offered free of charge and is not legally binding.*

These documents replace former issues